

LPR ONPREM RACK MOUNT SERVER

HARDWARE

TECHNICAL SPECIFICATIONS

AIS-SVPRM-RM



Feature	Technical specification
Form factor	1U rack server
Dimensions and weight	H: 42.8 mm (1.67 in), W: 434.0 mm (17.09 in), D: 495 mm (19.5 in) w/o ear, w/o bezel Max weight: 10.6 kg (20.96 lb)
Processor	1 processor • Intel® Xeon® processor E3-1200 v6 product family
Chipset	Intel C236
Operating system	Microsoft® Windows Server® 2016,
Memory	Architecture: Up to 2400MT/s DDR4 DIMMs Memory type: UDIMMs Memory module sockets: 4 Maximum RAM: Up to 64GB
Drive bays	2 x 3.5" cabled HDD 4 x 3.5" cabled HDD 4 x 3.5" hot-swap or 2.5" hot-swap in hybrid drive carrier
Slots	2 x PCIe 3.0 slots: x16 slot, full-height (1x8 3.0)+ x8 slot, low-profile (1x4 3.0)
Network controller	Broadcom® 5720
Communications	2 x 1GbE LOM
Power	250W cabled PSU
Device access	5 total USB: Rear: 2 x USB 3.0 ports Front: 2 x USB 2.0 ports Internal: 1 x USB 3.0 port
Rack support	ReadyRails™ static rails for tool-less mounting in 4-post racks with square or unthreaded round holes or tooling mounting in 4-post threaded and 2-post racks.
AIS-SVPRM-RM	16 cameras server Rackmount, 32 GB RAM, 4x1TB RAID storage, os win 2016 x64, 1GB NIC